

QUARZO

ANTIQUÉ EFFECT PAINT



DESCRIPTION

Quarzo is a decorative finish, made of metallic charges that permit to achieve a pleasant antique wall effect.

RECOMMENDED FOR

Interior applications on plaster, embossed wall coverings, gypsum board, concrete, cement rendering, brickwork & block work.

KEY FEATURES

- Resistant to shocks and abrasion
- Water based
- Easy to apply
- Wide range of color combinations

PHYSICAL PROPERTIES

Solvent Type	Waterborne
Finish Type	Matt finish based on ASTM D523
Spreading Rate	Approximately 5 m ² /kg/coat – 1 coat required
Average Dry Time	3 - 4 hours based on ASTM D 1640
Recoat	24 - 36 hours
Flash Point	None
Dry Film Thickness	Up to 50 - 100 microns, depending on application technique
Thinner	No thinning required
Adhesion	Classified 4B based on ASTM 3359-B for excellent adhesion
Scrub Resistance	>4,000 cycles based on EN 13300, formally DIN 53778S
Density	1.02 g/cm ³
VOC	Very low VOC content - Compliant with EU 2010 regulations maximum of 30 g/L.
Bases	1100 Gold, 1112 Gold & Silver, 1113 Gold & Copper, 1116 Silver & Black, 1119 Bronze & Black
Additives	No additive needed

SURFACE PREPARATION

All surfaces must be cured, clean, dry, and free from dirt, dust, rust, stains, grease, oil, mildew, wax, efflorescence, bond-breakers, and other contaminants. Remove all loose, peeling, or chalky paint by sanding, scraping, or other appropriate methods. Repair all cracks, holes, and other surface imperfections with a suitable patching material. Repaired surfaces should then be sanded smooth and dusted clean. When required prime the surface with a suitable Colortek primer.

New plaster or masonry surfaces must be allowed to cure (28 days) before applying base coat. Cured plaster should be hard, have a slight sheen and maximum pH of 10; soft, porous or powdery plaster indicates improper cure. Never sand a plaster surface; knife off any protrusions and prime plaster before and after applying patching compound. Poured or pre-cast concrete with a very smooth surface should be etched or abraded to promote adhesion, after removing all form release agents and curing compounds. Remove any powder or loose particles.

CAUTION: Scraping or sanding surfaces of older buildings (especially pre-1978) may release dust containing lead or asbestos. EXPOSURE TO LEAD OR ASBESTOS CAN BE VERY HAZARDOUS TO YOUR HEALTH. Always wear appropriate personal protective equipment during surface preparation, and finish cleanup of any residues by water-washing all surfaces.

QUARZO

ANTIQUÉ EFFECT PAINT



PRIMER SYSTEMS

SURFACE TYPE	RECOMMENDED COLORTEK PRIMER
Drywall	Colortek Primer
Porous Masonry	Colortek Sealer, Colortek Primer
Non-Porous Masonry	Colortek Primer or Colortek Undercoat
Wood	Colortek Undercoat or Colortek Wood Primer
Metal	Colortek Adhero, Adhero Quick Dry, SX47 StopRust, AquaZinc

APPLICATION CONDITIONS

Do not apply at temperatures below 5 °C or when rain is expected.

APPLICATION METHOD

Apply 2 coats of CoAcryl or CIA on the properly primed and cleaned surface.

Apply Quarzo with a brush using crisscross strokes. Then create the effect by smoothing the surface with a plastic spatula 10 to 15 minutes after application.

PACK SIZE

- 1 US Quart – 1 kg
- 1 US Gallon – 2.5 kg

SHELF LIFE

24 months from the date of production.

STORAGE AND HANDLING

Care should be taken to avoid spillage. Store in a dry area. Protect from freezing. Extreme temperatures may cause paint to become unusable. For example: freezing and thawing may cause paint to gel, and high heat may cause solid skin to form.

SAFETY

Use under well ventilated conditions. Do not breathe or inhale spray mist or sanding dust. Avoid skin contact; spillage on the skin should immediately be removed with suitable cleanser, soap and water. In case of eye contact, flush immediately with water for at least 15 minutes and seek medical attention immediately. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

CLEANING

Remove as much leftover product as possible from the application equipment before cleaning. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Do not empty product into drains or watercourses.

TECHNICAL ASSISTANCE

Available through your local COLORTEK® Design Center or through your COLORTEK PAINTS® authorized distributor. For the location of the retailer nearest you, email us at info@colortek.eu or check our website www.colortek.eu.

DISCLAIMER

Product batches are subject to stringent quality control checks in conformity with ISO 9001:2008, Certificate CH12/1128.

The information submitted in this manual is correct to the best of our knowledge & experience. No liability whatsoever can be accepted on the basis of the information supplied herein.